



Recommended PCB Layout
[TOP VIEW]

SPECIFICATIONS

- Voltage Withstanding : AC 1000V For 1 Minute
- Insulation Resistance: 300M Ω Min At 500V DC
- Contact Resistance : 20 Milliohms Max.
- Insertion Force : 8.5 Kg Max.
- Withdrawal Force : 1-5Kg
- 1-Socket Case : SPCC-SD 0.4t,Nickel Plated
- 2-Insulator : P.B.T,UL 94V-0
- 3-Earth Terminal : Pbr-H 0.25t,Pb10%,Sn 90%
- 4-Contact Terminal : Brass 0.7t,Pb 10%, Sn 90%
- 5-Rivet : AL ,Nickel Plated

Arrangement of Contacts				
Pin No.	04	06	07	08
Hole Layout				

MERITEC
<http://www.meritec.co.kr>

CATEGORY	Din Jack	APPROVED BY	MCI	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X ± 0.30 XX ± 0.25 AWG.
PART No.	DJXXD	CHECKED BY	RAN	
DRAWING No.	DJXXD	DRAWING BY	LXH	
SCALE	NONE	RFY.	A1	
UNIT	mm			NO. REV.

A1	Del Drawing:Pin No.5	BFCKY	2004/08/03
A1	Modify Spec. 1-3.5kg - 1-5kg	BFCKY	2004/08/03
A1	Modify Spec. 4.0kg - 6.5kg	BFCKY	2004/08/03
A1	Add Drawing	BFCKY	2004/08/03
AD	NEW RELEASE		
	REVISIONS	CHK	DATT