



SPECIFICATIONS

Current Rating: 5 Amperes
 Dielectric Withstanding Voltage: AC 1000V R.M.S.
 Insulation Resistance: 5000 Megohms At DC 500V
 Contact Resistance: 15 Milliohms Max.
 Operating Temperature: -55°C To $+105^\circ\text{C}$
 Contact Insertion Force: 341g Max.
 Contact Separation Force: 20g Min.
 Contacts: Brass Machine Pin, Gold Flash
 Insulator: PBT, UL 84V-0 Rated
 Shell: Cold Roller Steel, Tin Plated

MERITEC

<http://www.meritec.co.kr>

CATEGORY	D-SUB	APPROVED BY	MFI	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE				
PART No.	HDDH15P7G	CHECKED BY	RAN	.X ± 0.38	A3	Modify HDDH1bP7 → HDDH1bP7B	INGRID	11/23/2007
DRAWING No.	HDDH15P7G	DRAWING BY	LXH	.XX ± 0.25	A7	HDCD15P7 → HDDH15P7	BFCKY	10/27/2005
SCALE	NONE	RFY.	A3	ANG.	A1	HDCD15PJ7 → HDCD15P7	MFI	01/18/2004
				UNIT	A	NEW RELEASE	RAN	
				MM	NO. REV.	REVISIONS	CHK	DATT