



Sold Plating	Option
1.8μ"	<input type="checkbox"/>
3μ"	<input type="checkbox"/>
6μ"	<input type="checkbox"/>
15μ"	<input type="checkbox"/>
30μ"	<input type="checkbox"/>
60μ"	<input type="checkbox"/>

RECOMMENDED P.C.B LAYOUT
TOP VIEW (COMPONENT SIDE)

MATERIALS:

1. Housing: Glass Filled NYLON66 UL94V-0
2. Insert: Glass Filled PBT UL94V-0
3. Shielding: 0.20mm Thickness Copper Alloy with Nickel Plated.
4. Contact: 0.40mm DIA Phosphor Bronze gold Plating Over Nickel.
5. Solder: 0.20mm Thickness Copper Alloy with Nickel Plated.

MERITEC
<http://www.meritec.co.kr>

REV.	A	UNIT	MM	SCALE	1=1	GENERAL TOLERANCE		DRAWN	DATE	DWG. NO.	TITLE
						XX ±	XX ±				
						XX ±	XX ±	CHECK	DATE	5921-S-A-2x1	5921-S-A-2x1
						XX ±	XX ± 0.15	APPROVE	DATE	PART NO.	
						XXX ±	XXX ± 0.10			RJ45-00170	